



# LASTOIS PISCINAS, BICOMPONENT WATERPROOFING SYSTEM FOR POOLS



## Descripción

## Aplication

Ideal for rehabilitation pool with cracks, leaks, chipped and any other deficiencies, it can also be applied to the execution of new works. It is also very suitable for waterproofing sources.

## Surface preparation

Should be clean, forged (minimum 20 days), dry and compact. Cracks and irregularities should be repaired prior to application of the system.

## Modes of application

## Clean up

With Epoxy Solvent



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:



# Data sheet

---

Colour/s

Density

Solid content in volume

Viscosity

Drying time

Open time

Adherence

Compressive resistance

Flexural strength resistance

Temperature of work

## Storage

---

1 years in original container, tightly closed, in a cool dry place, protected from the weather.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

