

Descripción



Application

Modes of application

Data sheet

Colour/s

Density

Solid content in volume

Aspect

Dry for repainting

Storage

Security



Indications of danger:

H225: H225: Highly flammable liquid and vapour.

H304: H304: May be fatal if swallowed and enters airways.

H312+H332: H312+H332: Harmful in contact with skin or if inhaled.

H315: H315: Causes skin irritation.

H319: H319: Causes serious eye irritation.

H335: H335: May cause respiratory irritation.

H373: H373: May cause damage to organs through prolonged or repeated exposure.

H412: H412: Harmful to aquatic life with long lasting effects.

Prudence advice:

P210: P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: P370+P378: In case of fire: Use ABC powder extinguisher for extinction.

P501: P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: EUH066:Repeated exposure may cause skin dryness or cracking.

EUH208: EUH208:Contains butyl acrylate, butyl methacrylate, methyl methacrylate. May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

