

REPAIS EFECTO MEMORIA, Water-repellent with prolonged effect.



Description

Resin based on oligomer siloxanes with nanoparticles with fractionated release. This innovation in the product formulation causes that part of the effect endures over time. Thus when the maintenance is done one part of the effect is always active.

Aplication

It is used as a colourless water-repellent treatment on surfaces of mortar, faced brick, faced concrete, natural and artificial stone, marble, granite and tiles.

Surface preparation

The support must be clean and dry, free of dust and loose particles. The reparation of cracks, fissures, defects in groutings, etc must be solved before product applying. It is necessary to protect all the supports which won't be treated because once the products becomes dry can't be removed by chemical means.

Modes of application

Shake the package before using.

- Apply by brush, roller or homogeneously sprayer.
- The application requires a very clean support and completely dry.





- It must be applied from top to bottom taking into account that the product can't drop, so the product quantity applied must be enought but not too much.
- If two layers are applied is suitable to apply in both surfaces moistened but this must be previouly verified in a not useful area.
- The application on stone requires a previous test to verify that the colour tone not changes and how much quantity of admitted product.

Clean up

The tools must be cleaned with DISOLUAIS N while the product is wet.

Data sheet

Colour/sColourless

CompositionSiloxanes in organic solvents and additives with nanoparticles.

Solid content> 10%

Density0,79 kg/lt

Humidity.of the support lower than 5%

Combustion pointhigher than 70°C

Performance

6 sqm/litre.

Storage

Three years in their original packages protected from the weather and keeping away from heating sources. Store in cool and dry places.



