



LASTOIS MS MULTIUSOS LIQUIDO, MULTIPURPOSE WATERPROOFING AGENT BASED ON POLYMER MS LIQUID



Descripción

LASTOIS MS MULTIUSOS LÍQUIDO is a waterproofing agent based on polymer MS with good waterproofing properties, high adherence on moistened supports, fast dry, very good resistance against the weather. Suitable for terrace, decks, roofs, chimney joints, corners, etc.

Aplication

LASTOIS MS LÍQUIDO is used for waterproofing decks, terraces, chimneys, deck edges, singular points, etc. Vertical and horizontal surfaces. It is able to stick on concrete, mortar, zinc, fiberglass, tiles, bricks, steel and aluminium.

Surface preparation

The surface must be done clean, dry or slightly wet, free of dust and loose particles.

Modes of application

Homogenize the content of the package.

- Prepare the support, sealing with LASTOIS MS in areas where are defects, joints, etc.
- Apply LASTOIS MS LIQUID by brush, roller or trowel.



- Apply it in two layers of 1,5 kg each one. For the application of the second one the first one must be completely dry.
- It can be reinforced with a fiberglass felt such as FIBRAIS 150.
- When it is dry another layer of LASTOIS MS must be applied.

Clean up

The tools must be cleaned with alcohol.

Data sheet

Composition Hybrid Polymers

Aspect Creamy

Density 1,4 kg/lit

Shore A hardness > 40, cured 60

Elongation upon breaking point 220% aprox

Temperature of service - 40°C at + 90°C

Performance

2,5 to 3 kg/sqm according use

Storage

Two years in their original packages protected from the weather and stored in a cool and dry place.

Security

Supplementary information:



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:




EUH066: Repeated exposure may cause skin dryness or cracking.


EUH208: Contains . May produce an allergic reaction.


EUH210: Safety data sheet available on request.




 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

 Telf.: 981 602 111

 Fax.: 981 601 508

 Email.: desarrollo@teais.es

síguenos en:

