



HIDROIMPER, Water repellent for facades, high capacity waterproofing for facades with porous surface.



Description

Aplication

Water repellent very suitable for stone facades, exposed brick, concrete, single-layer mortars, lime mortars, plasters, etc. Does not change the aesthetic appearance and maintains the breathability of the façade

Surface preparation

Support must be at least 28 days old. Totally clean, free of dust, paint, coatings. It cannot be used in permanent contact with water, on horizontal surfaces, or on surfaces below the water table. Cracks and fissures must be repaired before application, since the waterproofing agent for facades does not bridge cracks. Avoid contact with doors, windows, aluminum surfaces, glass, tiles, etc. The entire surface that is not going to be impregnated must be protected.

Modes of application



Avda. da Enerxía, nº 153, PoL Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:



Clean up

The tools are cleaned with cleaning solvent with the fresh product.

Data sheet

Aspect

Composition

Density

Solid content

Humidity.

Temperature of work

Storage

1 year in its original well-closed containers, stored in a cool and dry place.

Security



Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs through prolonged or repeated exposure .

H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+P378: In case of fire: Use ? for extinction.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.



Avda. da Enerxía, nº 153, PoL Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en: