

DISOLVENTE EPOXI, EPOXI PAINT THINNER



Descripción

Universal solvent for all kinds of epoxy resins based paints. Semi-fast, allows applications by spray gun or brush.

Aplication

To dilute epoxy paints and cleaning tools. To dilute and clean all solvent epoxy systems

Surface preparation

Not applicable

Modes of application

Apply to all kinds of epoxy paints. For cleaning tools for use with epoxy paints.

Clean up

Not applicable





Data sheet

Density0,875 Kg/L. (+-) 0,025

Performance

According to use.

Storage

3 years stored in a dry and cool place.

Security







Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H332: Harmful if inhaled.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H373: May cause damage to organs through prolonged or repeated exposure.

Prudence advice:





P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: In case of fire: Use? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.



