



## Descrição

Sythetic water-based paint, high quality, for optional finishing on floorings with ESLURRIS synthetic or asphaltic. Also, it can be applied on concrete and asphalt, on sport courts, garages, boardwalks, etc. Resistant to weather. Colours: red and green.

## Aplication

As a finishing paint on ESLURRIS.

## Surface preparation

The support must have proper mechanical resistance. It must be cleane, cured, free of dust, loose particles, greases and oils.

## Modes of application

Homogenize well the content of the package stiring it manually or with a low revolution electric mixer (300-500 rpm).

- Apply a thin coat by brush, roller or gun.
- Let it dry completely and apply a second coat. The drying time is about 12 hours at 20°C and 65% RH.
- The support of application must be completely dry, free of dust or loose particles.

- Don't apply whit rain forecast, freezes or strong wind.

## Clean up

with plenty of clean water while the product is wet. Once it hardens only can be removed by mechanical means.

## Data sheet

Density 1,38 Kg./Lt.  $\pm$  0,05

Viscosity 30.000  $\pm$  10.000 mPa.s

Solubility soluble in water

Temperature of work from 8 to 25 °C

Dry upon touching 1 Hour at 20°C/65% of R.H.

Colour/s Red and green. Others under order.

## Performance

5 sqm per kg and coat according to the absorption.

## Storage

2 years in their original packages, tightly closed, avoiding extreme temperatures and protected from the weather.

## Security


## Supplementary information:

EUH208: EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teis.es

síguenos en:



EUH210: EUH210:Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

