PINLURRIS, ACRYLIC-BASED FLOOR PAINT



Description

Sythetic water-based paint, high quality, for optional finishing on floorings with ESLURRIS synthetic or asphaltic. Also, it can be applied on concrete and asphalt, on sport courts, garages, boardwalks, etc. Resistant to weather. Colours: red and green.

Aplication

As a finishing paint on ESLURRIS.

Surface preparation

The support must have proper mechanical resistance. It must be cleane, cured, free of dust, loose particles, greases and oils.

Modes of application

Homogenize well the content of the package stiring it manually or with a low revolution electric mixer (300-500 rpm).
- Apply a thin coat by brush, roller or gun.
- Let it dry completely and apply a second coat. The drying time is about 12 hours at 20ºC and 65% RH.
- The support of application must be completely dry, free of dust or loose particles.

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

- Don´t apply whit rain forecast, freezes or strong wind.

Clean up

with plenty of clean water while the product is wet. Once it hardens only can be removed by mechanical means.

Data sheet

Density1,38 Kg./Lt. ± 0,05

Viscosity30.000 +- 10.000 mPa.s

Solubilitysoluble in water

Working temperaturefrom 8 to 25 ºC

Touch Dry1 Hour at 20ºC/65% of R.H.

Color(s)Red and green. Others under order.

Performance

5 sqm per kg and coat according to the absorption.

Storage

2 years in their oringinal packates, tightly closed, avoiding extrem temperartures and protected from the weather.

Security

Supplementary information:

EUH208: EUH208:Contains . May produce an allergic reaction.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

EUH210: EUH210:Safety data sheet available on request.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: