



Descripción

Application

Modes of application

Data sheet

Density

Viscosity

Thin layer

Dry upon touching

Temperature of work

Dry for repainting

Storage

Security



Indications of danger:

- H225: Highly flammable liquid and vapour.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H340: May cause genetic defects .
- H350: May cause cancer .
- H362: May cause harm to breast-fed children.
- H373: May cause damage to organs through prolonged or repeated exposure .
- H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

- P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313: IF exposed or concerned: Get medical advice/attention.
- P370+P378: In case of fire: Use ? for extinction.
- P501: Dispose of contents/container in accordance with local/regional/national/international regulation