

### **DURIMPRES, COLOURING POWDER AND** HARDENER USED FOR STAMP CONCRETE **PAVEMENTS**



## Descrição

Colouring powder and surface hardener for printed concrete paving that is applied onto the fresh concrete mix. It hardens concrete and colour it at the same time.

Colours: grey. Other colours price according with colour and amount of order. Colour chart.

# **Aplication**

It is used for hardening and colouring stamped concrete.

#### **Surface preparation**

The product is applied onto the fresh concrete until fully covering the support. Leave to act during some minutes.

#### **Modes of application**

The powder product is spread onto the fresh concrete until it is uniformly applied. Leave to act for a couple of minutes.

Apply the powder releasing agent DESPOL.





Place the mould on the surface of the fresh concrete mix. Once the concrete hardens, remove the mould.

#### Clean up

When using a tool during the application, clean using water and leave to dry before using again.

## **Data sheet**

Density1.25 kg/L  $\pm$  0.05 g/cc

Colour/sWide range of colours.

Composition quartz aggregates, special cements, inorganic pigments, additives.

Average thickness2 to 2.5 mm for consumption of 4 kg / m2 aprox

% Solid content in weight

Temperature of work5 to 30°C

#### **Performance**

3 to 5 kg per m2

### **Storage**

It is recommended to store this product for 2 years in tightly closed original packages.



