



# DURIMPRES, COLOURING POWDER AND HARDENER USED FOR STAMP CONCRETE PAVEMENTS



## Descripción

Colouring powder and surface hardener for printed concrete paving that is applied onto the fresh concrete mix. It hardens concrete and colour it at the same time.

Colours: grey. Other colours price according with colour and amount of order. Colour chart.

## Aplication

It is used for hardening and colouring stamped concrete.

## Surface preparation

The product is applied onto the fresh concrete until fully covering the support. Leave to act during some minutes.

## Modes of application

The powder product is spread onto the fresh concrete until it is uniformly applied. Leave to act for a couple of minutes.

Apply the powder releasing agent DESPOL.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teis.es](mailto:desarrollo@teis.es)

síguenos en:



Place the mould on the surface of the fresh concrete mix.  
Once the concrete hardens, remove the mould.

## Clean up

---

When using a tool during the application, clean using water and leave to dry before using again.

## Data sheet

---

Density 1.25 kg/L  $\pm$  0.05 g/cc

Colour/s Wide range of colours.

Composition quartz aggregates, special cements, inorganic pigments, additives.

Average thickness 2 to 2.5 mm for consumption of 4 kg / m<sup>2</sup> aprox

% Solid content in weight

Temperature of work 5 to 30°C

## Performance

---

3 to 5 kg per m<sup>2</sup>

## Storage

---

It is recommended to store this product for 2 years in tightly closed original packages.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teis.es](mailto:desarrollo@teis.es)

síguenos en:

