



Descripción

Transparent liquid based on parafins emulsion for working as protection membrane of cement curing on concretes and wet mortars.

Aplication

Its application to newly laid concrete floors, forms a film that prevents premature loss of water. Without altering the setting time. As protector for curing fresh cement and mortar. Improves physical resistances.

Surface preparation

Not applicable.

Modes of application

Mix the content of the package before so as to make it uniform.

- Apply directly onto the mortar or concrete with a spray.
- It is recommended to apply in two continuous coatings.

Application is only possible once it is observed that the surfaces of application become matt.

- Surfaces to be finished with mortar or paint must not be treated with LACURIS A or proceed to sanding the surface to ensure proper adhesion.

Clean up

Clean tools and spray equipment with Disolvente de Limpieza immediately after using.

Data sheet

Colour/scloudy white

Density 0.98 gr/ml. At 20 ° C

Performance

8 sqm per l (min).

Storage

2 years in their original packagings, properly closed and at moderated temperatures, stored in a dry and cool place.

Security

Supplementary information:

EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teis.es

síguenos en:

