PROTECTOR TEAIS-MICROCEMENTO, SPECIAL PROTECTOR FOR THIN PORE SURFACES



Description

Special protector for applying over TEAIS-MICROCEMENT soils. The protector provides more resistance to wearing, seal micropores and improves the stetic of pavement.

Aplication

It is used for protecting pavements, walls, worktops, etc cladding with TEAIS MICROCEMENT. Suitable in outdoors and indoors. It also can be used for the natural and artificial stone surfaces, etc.

Surface preparation

The surface must be clean and slightly wet in the moment of application.

Modes of application

The support must be dampened homogeneouly and when the moisture decreases, the applied of theprotector must done. Don´t apply on dry supports. The wetting of the support can be done with hose or planty and homogeneous spraying.
-Shake in order to homegenize properly the product.

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

-Apply with short nap roller after the first coat is dry.
-The dry time until the second application must be one hour and is recommendable to testing before applying the second coat in order to avoid the darknening.
-To the application on stone is recommended to testing before in order to check that the aestethic appearance is the same.

Clean up

The tools must be cleaned with cleaning solvent while the product is wet.

Data sheet

Density0,83 kg/lt

Color(s)Cloudy translucent.

OdorTypical.

Recoatable1 hour al 20º 65% RH

Touch Dry30 minutes at 20ºC 65%RH

Working temperatureFrom 8º to 25º

n/aOrganic solvents mixing.

Performance

5 to 6 m2/lt

Storage

Two years in their original packages protected from the weather stored in cold and dry places.

Security



TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

Indications of danger:

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: In case of fire: Use ? for extinction.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains . May produce an allergic reaction.