



PROTECTOR TEAIS-MICROCEMENTO, SPECIAL PROTECTOR FOR THIN PORE SURFACES



Description

Special protector for applying over TEAIS-MICROCEMENT soils. The protector provides more resistance to wearing, seal micropores and improves the stetic of pavement.

Aplication

It is used for protecting pavements, walls, worktops, etc cladding with TEAIS MICROCEMENT. Suitable in outdoors and indoors. It also can be used for the natural and artificial stone surfaces, etc.

Surface preparation

The surface must be clean and slightly wet in the moment of application.

Modes of application

The support must be dampened homogeneously and when the moisture decreases, the applied of the protector must done. Don't apply on dry supports. The wetting of the support can be done with hose or planty and homogeneous spraying.

-Shake in order to homegenize properly the product.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



- Apply with short nap roller after the first coat is dry.
- The dry time until the second application must be one hour and is recommendable to testing before applying the second coat in order to avoid the darkening.
- To the application on stone is recommended to testing before in order to check that the aesthetic appearance is the same.

Clean up

The tools must be cleaned with cleaning solvent while the product is wet.

Data sheet

Density 0,83 kg/l

Colour/s Cloudy translucent.

Odour Typical.

Dry for repainting 1 hour at 20° 65% RH

Dry upon touching 30 minutes at 20°C 65% RH

Temperature of work From 8° to 25°

Vehicle Organic solvents mixing.

Performance

5 to 6 m²/lt

Storage

Two years in their original packages protected from the weather stored in cold and dry places.

Security



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:



Indications of danger:

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: In case of fire: Use ? for extinction.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teis.es

síguenos en:

