



# TEAIS PAVIFORTE, Hardening liquid treatment and consolidating.

## Descripción

Liquid treatment with consolidant effect to apply on concrete pavements. It hardens deeply keeping the aesthetic appearance. Suitable for industrial pavements, cementitious pavements. Improves the resistance against abrasion and has anti-dust effect.



## Aplication

TEAIS PAVIFORTE is used for surface consolidation of concrete and polished-concrete industrial pavements. Warehouses, shopping centers, parkings, etc. Improves the resistance to abrasion on cementitious pavements. Improves the resistance to

## Surface preparation

The support must be clean, free of dust, particles. The support must be consisting. It shouldn't have greases and oils. The surface must be dry, without humidity and water.

## Modes of application

Teais Paviforte can be applied after 2 or 3 days of concrete pouring or joint cutting.  
- In the case of already cured joints it is applied directly on the clean and dry support and free of treatments or paints or any other substances which may hinder the penetration fo consolidating treatment.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:



- It can be applied by pouring directly on the floor homogeneously. Is necessary to avoid dry and wet zones at the same time. The liquid must be onto the support between 20 and 30 minutes.
- Once the time has past the excess of liquid must be removed drying and polishing the treated surface.
- Finishing the spreading and drying operation is suitable to don't walk at least for a couple of days on it.
- It is recommended to do a previous test in order to check the consumption of the product.

## Clean up

Tools must be cleaned while the material is fresh.

## Data sheet

Colour/s Translucent liquid

Density 1,12 kg/lt

PH 11

Temperature of work from 5°C to 30°C

## Performance

200 to 400 grs/sqm according support absorption

## Storage

One year in their original packages protected from the weather and stored in cool and dry places.

## Security



## Indications of danger:

H315: Causes skin irritation.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teis.es

síguenos en:



H319: Causes serious eye irritation.

## Prudence advice:

---

P264: Wash ? thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

