



## Descripción

Coating based on stabilizer plastic resins and marble grane prepared to be applied with stainless steel trowel and with a 2mm of thickness. Decorative coating on vertical and horizontal walls for indoor and outdoor. Colours available: colour chart. The minimum quantity to order is 115 kgs. Consult prices for higher or smaller quantities.

## Aplication

Soapstone decorative coating for horizontal or vertical surfaces indoors or outdoors. Ideal for decorating facades, stores, stairwells, cafeterias, hotels, restaurants, etc..

## Surface preparation

The application surface has to be clean and dry, in the case of cement mortar they should be cured in 28 days at least.

## Modes of application

IMPERGRAIS primer package content must be homogenized.

-Apply one hand of IMPERGRAIS diluted in wáter in relation of 1:5. The application is done with roller or brush. With this procedure more adherence of GRAIS is achived on the support and more waterproofing.

-Let dry properly the primer before applying the coating.

- Shake properly the content of the GRAIS package before using until forming foam.
  - The product is applying by a stainless-steel trowel avoiding waves and marks with trowel's edge.
  - The applied layer must have an uniform thickness of 2mm. The layer thickness comes by aggregates particle sizes.
  - The edges are obtained with a trowel in vertical position beside the borders in one of the two sides and with the paddle in the other hand, pressing the material with the trowel making the edge.
  - When the material looks like less milky , all the unevenness of the material must be repaired and equalized. This equalized and repaired material is obtained with the trowel and de paddle very clean and wet, pressing on the surface.
  - The application must be continuous. But if it is necessary make a previously división with adhesive tape fitting stright mounting the coating on it and then remove it. For cutting up the parameters it is painted with ACRILAIS in the desired colour on 30mm width stripes and once dry the adhesive tape must be sticked. Apply GRAIS on all the Surface and once it is smoothed remove the adhesive tape with the material which is on it obtaining in this way the cuttings.
  - Application surfaces have to be completely cured (more than 28 days dried) and dry, in addition all the smoothing details must be corrected before application.
- Don't apply with rain forecast, with high winds, with high temperatures, frosts or any adverse weather condition.

## Clean up

With plentiful clean water, while the material is fresh, after hardened it will only can be removed by mechanical means.

## Data sheet

Density 1,97 g/cc

Solid content in volume 81,17%

Adherence > 1 N/mm<sup>2</sup>

Colour/s Look Colour chart.

Composition Marble grain with continuing grading and resins in watery emulsion.

Temperature of work From 5 to 30°.

Totally dry 3 days at 20°.

ZZZ

ZZZ

ZZZ

ZZZ



ZZZ

ZZZ

## Performance

From 3 to 4 kg/sqm on 2mm layer.

## Storage

Store in a cool dry for 1 year at most, well protected from weather.

## Security

### Indications of danger:

H412: H412Harmful to aquatic life with long lasting effects.

### Prudence advice:

P271: P271:Use only outdoors or in a well-ventilated area.

P501: P501:Dispose of contents/container in accordance with local/regional/national/international regulation

### Supplementary information:

EUH208: EUH208:Contains Mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:

