



# RELAIS, ACRYLIC RENDER FINISH WITH AGGREGATE FOR INDOOR AND OUTDOOR



## Descripción

Grating paste, made of vinyl resins and graded fillers (TYPE F of 1mm and TYPE G of 2mm). It has a strong resistance to the passing of time. It is suitable for the protection of interior and exterior supports in homes, premises, etc.

## Aplication

Render for façades, courtyards, staiRwells, both indoors and outdoors.

## Surface preparation

The background of application must be clean, free of grease, oil or loose particles. Once the support is sound, IMPRIMAIS primer is applied.

## Modes of application

Mix it manually or mechanically using a low speed mixer (400 - 500 rpm).

- Apply our primer IMPRILAIS by roller or brush.
- Let the primer dry completely.
- Apply with stainless steel trowel and then, once extended the product, when it starts to dry, work with a



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: desarrollo@teais.es

síguenos en:

trowel by moving it in vertically, horizontally or in circles until producing the desired travertine or circular patterns.

- The support of application must be clean, free of grease, oil or loose particles.
- Mortars must be allowed to cure for at least 28 days.
- Do not apply when rain, freezing temperatures and other bad weather conditions are expected.

## Clean up

Clean using large amounts of water.

## Data sheet

Density G.F....1.9 ± 0.07 g/cm<sup>3</sup> at 20°C  
G.G...1.87 ± 0.05 g/cm<sup>3</sup> at 20°C

Colour/s

Aspect matt textured

Viscosity 48.000 ± 16.000 mPa.s

Temperature of work 5 to 30 °C

Totally dry 3 days at 20°C

zzzzzz

zzzzzz

zzzzzz

zzzzzz

zzzzzz

zzzzzz

## Performance

F (thin finish): 1,5 - 2 kg per m<sup>2</sup>

G (thick finis

## Storage



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:



It is recommended to store this product for 1 year at most in tightly closed original packages.

# Security



## Indications of danger:

H317: May cause an allergic skin reaction.

## Prudence advice:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation