



# REVOGACAL RUSTICO, LIME BASED RENDER FOR BASE LAYER



## Descripción

Traditional lime-based rendering that has powder appearance to mix with water. REVOGACAL RÚSTICO has a suitable particle-size to form levelling layers.

The applied and dry mortar has an excellent transpirability what provides healthy, dry and disinfected by the action of the lime of mortar. White colour.

Can be used as base layer to finish on with REVOGACAL or ESTUCAL SATINADO.

## Aplication

To make base layers in refurbishment or based-lime mortars with several finishes such as estucco, etc

## Surface preparation

Free of dust and greases with a correct planimetry, without fissures, with high mechanical resistance and with the supports slightly moistened.

## Modes of application

The product has to be blended with water in 25% on weight and must be let stand for 10 minutes before its application.

- Spread the lime mortar on the wall slightly moistened by a trowel and a average thickness from 6 to 12 mm. Subsequently the surface must be even and finishh.

## Clean up



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email.: desarrollo@teais.es

síguenos en:



With plenty of water while the material is wet. Once it hardens only can be removed by mechanical means.

# Data sheet

Water absorption 25% + - 0,05

Powder density 1,35 kg/lt

Mass of density 1,75 kg/lt

Open time 2 1/2 3 hours

Adherence > 3 kg/cm

Compressive resistance 38 kg/sqm

Flexural strength resistance 15 kg/sqm

Temperature of work from 5°C at 30°C

Colour/s white and other under order

Composition

## Performance

1,4 kg per sqm of 1 mm of thickness

## Storage

2 years in their original packages tightly closed, stored in cool and dry places.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:

