AUTAIS IMPRI, FAST-DRY PRIMER



Description

Fast dry-time antirust primer for the protection of metallic surfaces before its finish with AUTAIS. Grey colour. Solvent: DISOLUAIS.

Aplication

As a primer and protection of car bodies, truck cabins, vans, bikes, farm machinery, tractor, etc.

Surface preparation

It must be clean, free of dust, greases, oils or other polluting agents which avoids a correct adherence on the supports and its perfect finish.

Modes of application

Stir well the content of the package before using.
- The surface of applycation must be clean, free of dust and to achieve this a suitable mechanical cleaning must be done by brushing, sanding or jets of particles removing the rust from metal. Also, the dust or any substance that avoids the correct adherence will be removed completely.
Apply one layer diluted from 10 to 30% on weight with DISOLUAIS by sprayer gun.
Allow 30 minutes (minimum) before applying the second layer in the same way.
Protect with a finis based on TEAIS synthetic enamels.

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

- For a correct dry, don´t apply with high humidity (>75%). Is recommendable to do the applycation in environments with a temperature up to 8ºC and bellow 35ºC.

Clean up

With grease-based solvent DISOLUAIS while the product is wet.

Data sheet

Density1,20 Kg./Lt. +- 0,05

Volume Solids39 ± 1 %

Viscosity150 +- 30 Sec.

Dry Hard< 1 hr at 20ºC and 65% RH

Color(s)grey

Recoatable30 minutes at 20ºC and 65 RH

Working temperaturefrom 8 to 35ºC

Performance

4 sqm per litre.

Storage

2 years in their original packages, tightly closed, stored in a fresh and dry place and protected from the weather.

Security



Indications of danger:

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

H226: Flammable liquid and vapour.

H312: Harmful in contact with skin.

H332: Harmful if inhaled.

H315: Causes skin irritation.

H340: May cause genetic defects.

H350: May cause cancer.

H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains . May produce an allergic reaction.