



## Descripción

Synthetic primer for subsequent enamel finishing on wooden supports, gypsum and plaster. Solvent: DISOLUAIS. Colour: White.

## Aplicación

As a primer for a subsequent finishing with synthetic enamel on wooden support. Seal and fill pores and a smooth surface is achieved where synthetic enamels having a better covering and colouring power, uniforming the absorption and finishing quality. It can be applied both on wood and repainting.

## Surface preparation

Must be quite clean, healthy, dry and free of greases, oils or any other polluting substance.

## Modes of application

Stir to homogenize good the content of the package.

- It must be applied by brush, roller or spray-gun.

A good layer must be applied in order to penetrate into the pores. Let it dry completely and sand it to achieve a smooth and uniform surface, with a homogeneous absorption and suitable as a synthetic enamels such as

ESMAIS or ESMAR.

- Before sanding at least 12 hours must pass in order to the primer be completely dry.
- After sanding all dust must be removed in order to let the support ready
- The application must be done with temperatures between 5° and 30°.

## Clean up

With TEAIS solvent DISOLUAIS, while the material is fresh. Once hardens only can be removed mechanically.

## Data sheet

Density 1,37 Kg./Lt. +- 0,05.

Dry for repainting 12 hours at 20°C 65% RH

Average thickness 45 microns per layer

Aspect Matt

Colour/s White

Temperature of work from 5 to 30°C

## Performance

5 sqm per litre

## Storage

2 years in their original packages, tightly closed, stored in a dry and cool place completely protected from the weathering.

## Security



## Indications of danger:



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:



H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H340: May cause genetic defects .

H350: May cause cancer .

H372: Causes damage to organs through prolonged or repeated exposure .

H412: Harmful to aquatic life with long lasting effects.

## Prudence advice:

---

P201: Obtain special instructions before use.

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

---

EUH066: EUH066:Repeated exposure may cause skin dryness or cracking.

EUH208: EUH208:Contains . May produce an allergic reaction.

