



Descripción

Special primer for suitable applying of RELAIS cladding. Apply just one coat diluted on water at 25%.

Available colours: According with RELAIS colour.

Aplication

As a primer to properly ensure the adhesion of our RELAIS plastic coating. It can be applied to both new surfaces and painted surfaces after preparation.

Surface preparation

Must be clean, without greases, oils, dust or loose particles, being compact, dry or slightly moistened.

Modes of application

Mix the content of each package thoroughly before using the product.

Apply using a paint brush or roller.

Dilute in water up to 50%(maximum) and then apply one single coating.

Leave to stand for at least 8 hours before applying RELAIS.

Clean up

With plentiful clean water while the product still fresh.

Data sheet

Density 1,67 Kg./Lt. +- 0,05

Viscosity 50.000 +- 10.000 mPa.s

Temperature of work 5 to 30°C

Dry for repainting 8 hours at 20°C

Colour/s Colour/s: regarding color chart

Performance

10 sqm per kg and per layer

Storage

2 years, in their original packages and properly closed, stored in a fresh and dry place and protected from the weather.

Security

Indications of danger:

H412: Harmful to aquatic life with long lasting effects.

Prudence advice:

P273: Avoid release to the environment.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

