# IMPRILAIS, SPECIAL PRIMER FOR RELAIS




## Descripción

Special prime for suitable applying of RELAIS cladding. Apply just one coat diluted on water at 25%.
Available colours: According with RELAIS colour.

## Aplication

As a primer to properly ensure the adhesion of our RELAIS plastic coating. It can be applied to both new surfaces and painted surfaces after preparation.

### Surface preparation

Must be clean, without greases, oils, dust or loose particles, being compact, dry or slightly moistened.

### Modes of application

Mix the content of each package thoroughly before using the product.
Apply using a paint brush or roller.
Dilute in water up to 50%(maximum) and then apply one single coating.
Leave to stand for at least 8 hours before applying RELAIS.

### Clean up

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

With plentiful clean water while the product still fresh.

# Data sheet

Density1,67 Kg./Lt. +- 0,05

Viscosity50.000 +- 10.000 mPa.s

Working temperature5 to 30ºC

Recoatable8 hours at 20ºC

Color(s)Colour/s: regarding color chart

## Performance

10 sqm per kg and per layer

## Storage

2 years, in their original packages and properly closed, stored in a fresh and dry place and protected from the weather.

# Security

## Indications of danger:

H412: Harmful to aquatic life with long lasting effects.

## Prudence advice:

P273: Avoid release to the environment.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

EUH208: Contains . May produce an allergic reaction.