



# IMPRILAIIS, SPECIAL PRIMER FOR RELAIS



## Description

Special prime for suitable applying of RELAIS cladding. Apply just one coat diluted on water at 25%.

Available colours: According with RELAIS colour.

## Application

As a primer to properly ensure the adhesion of our RELAIS plastic coating. It can be applied to both new surfaces and painted surfaces after preparation.

## Surface preparation

Must be clean, without greases, oils, dust or loose particles, being compact, dry or slightly moistened.

## Modes of application

Mix the content of each package thoroughly before using the product.

Apply using a paint brush or roller.

Dilute in water up to 50%(maximum) and then apply one single coating.

Leave to stand for at least 8 hours before applying RELAIS.

## Clean up



Avda. da Enerxía, nº 153, PoL Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:



With plentiful clean water while the product still fresh.

# Data sheet

Density 1,67 Kg./Lt. +- 0,05

Viscosity 50.000 +- 10.000 mPa.s

Temperature of work 5 to 30°C

Dry for repainting 8 hours at 20°C

Colour/s Colour/s: regarding color chart

## Performance

10 sqm per kg and per layer

## Storage

2 years, in their original packages and properly closed, stored in a fresh and dry place and protected from the weather.

## Security

### Indications of danger:

H412: Harmful to aquatic life with long lasting effects.

### Prudence advice:

P273: Avoid release to the environment.



Avda. da Enerxía, nº 153, PoL Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email.: desarrollo@teais.es

síguenos en:

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## **Supplementary information:**

EUH208: Contains . May produce an allergic reaction.