IMPRIMAIS MR, FAST-DRY ANTIRUST PRIMER.



Description

Fast dry time antirust primer for protecting metallic surfaces.
Solvent: DISOLUAIS. Colours: Red, Grey and Black.

Aplication

As a primer and protection of car bodies, truck cabins, vans, bikes, metallic structures, etc

Surface preparation

The surface must be clean, free of dust, greases, oils and other polluting agents that avoids a good adherence on the supports and a perfect finish.

Modes of application

Shake well the content of the package before using.
Once the surface iscleaning up, dry and free of rust, prime with diluted layer from 10% to 30% with DISOLUAIS by spray gun.
Allow 30 minutes (minimum) and apply a second layer by the same way.
- Allow it dry at least 8 hours at 20ºC for applying the finishing.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

Protect with a finish based on synthethic enamels ESMAIS AND ESMAR.

Clean up

With grease- based solvent DISOLUAIS.

Data sheet

Density1,27 Kg./Lt. +- 0,05

Volume Solids47 ± 1 %

Flash Pointup to 25 ºC

Touch Dry< 2 Hours

Recoatable4 Hours /20ºC/65% (with enamels).

Dry Film Thickness25 microns minimum

Working temperaturefrom 5ºC to 30ºC

Color(s)Malaga Red

Performance

5 sqm per litre.

Storage

2 years in their original packages and tightly closed, stored in a dry and cool place and protected from the weaher.

Security



Indications of danger:

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H340: May cause genetic defects .

H350: May cause cancer .

H372: Causes damage to organs through prolonged or repeated exposure .

H373: May cause damage to organs through prolonged or repeated exposure .

H411: Toxic to aquatic life with long lasting effects.

H200: Unstable explosives.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains . May produce an allergic reaction.