



## Descrição

Fast dry time antirust primer for protecting metallic surfaces.  
Solvent: DISOLUAIS. Colours: Red, Grey and Black.

## Application

As a primer and protection of car bodies, truck cabins, vans, bikes, metallic structures, etc

## Surface preparation

The surface must be clean, free of dust, greases, oils and other polluting agents that avoids a good adherence on the supports and a perfect finish.

## Modes of application

Shake well the content of the package before using.

Once the surface is cleaning up, dry and free of rust, prime with diluted layer from 10% to 30% with DISOLUAIS by spray gun.

Allow 30 minutes (minimum) and apply a second layer by the same way.

- Allow it dry at least 8 hours at 20°C for applying the finishing.

Protect with a finish based on synthetic enamels ESMAIS AND ESMAR.

## Clean up

With grease- based solvent DISOLUAIS.

## Data sheet

Density 1,27 Kg./Lt. +- 0,05

Solid content in volume 47 ± 1 %

Combustion point up to 25 °C

Dry upon touching < 2 Hours

Dry for repainting 4 Hours /20°C/65% (with enamels).

Dry film thickness 25 microns minimum

Temperature of work from 5°C to 30°C

Colour/s Malaga Red

## Performance

5 sqm per litre.

## Storage

2 years in their original packages and tightly closed, stored in a dry and cool place and protected from the weather.

## Security



## Indications of danger:



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:



H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H340: May cause genetic defects .

H350: May cause cancer .

H372: Causes damage to organs through prolonged or repeated exposure .

H373: May cause damage to organs through prolonged or repeated exposure .

H411: Toxic to aquatic life with long lasting effects.

H200: Unstable explosives.

## **Prudence advice:**

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## **Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains . May produce an allergic reaction.