



IMPRIMAIS MU, FIXING AND SEALANT SOLVENT-BASED PRIMER.



Description

Solvent-based primer for fixing water-based plastic paints on new building, fiber cement, tiles, old paint in good conditions and for all types of surfaces in general except the glazed surfaces. Shake before using. Solvent: DISOLUAIS.

Application

On painted surfaces (indoors and outdoors) in good condition. When they are in bad condition with flakes, blisters, etc must be removed. On tiles, fiber cement or similar. On old coverings and materials that require superficial hardening. In general on all types of surfaces except glazed.

Surface preparation

Remove manually the old and deteriorated paint layers, being clean, dry and free of dust and loose particles.

Modes of application

Homogenize the content of the package before using.

- Don't dilute it.
 - It is applied by brush or roller.
- It only can be repainted with water-based plastic paints.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:

Apply on the support one layer and wait 24 hours to paint again with plastic paints.

- Can be used both in indoors and outdoors.
- For outdoors not apply with rain forecast, strong winds, freezes or any adverse weather condition.

Clean up

with DISOLUAIS SOLVENT.

Data sheet

Density 0,80 Kg./Lt. +- 0,02

Viscosity 18 +- 6 Sec.

Aspect Matt

Colour/s Translucent

Temperature of work from 5 to 30°C

Performance

From 5 to 7 sqm per litre.

Storage

2 years in their original packages tightly closed, stored in a dry and cool place protected from the weather.

Security



Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312: Harmful in contact with skin.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H362: May cause harm to breast-fed children.

H372: Causes damage to organs through prolonged or repeated exposure .

H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.