



## Description

Water-based primer very thin particle-size to be applied on new supports that requires good adherence. It makes the subsequent painting easier at the same time that reduces the quantity of paint to using. Apply diluted in water in proportion of 1 to 5.

## Aplication

As the preparation of primers in new covering, cement and gypsum. Seals and penetrates quite good.

## Surface preparation

The surface must be clean, free of greases and dry.

## Modes of application

Shake strongly the product before applying.

Apply with brush or roller diluted in proportion until 1:5 with water.

- If it is used in outdoor not apply with rain forecast, strong winds, freeze or any adverse wheather condition.

## Clean up

with plenty of clean water.

# Data sheet

Density 1,05 Kg/L. (+-) 0,05 at 20°C

Viscosity 12,5 ± 2,5 seg. At 20°C. Layer Ford: 4 mm

Dry upon touching < 30 min. at 20°C, 65% R.H.

Dry for repainting after 8 hours at 20°C y 65% RH

Temperature of work from 5°C to 30°C

ZZZ

ZZZ

## Performance

25 sqm per litre.

## Storage

Store in a dry and cool place for 2 years maximum in their original packages and tightly closed.

## Security



### Indications of danger:

H317: May cause an allergic skin reaction.

### Prudence advice:



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:



P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

