IMPRIMACION INTUMESZAIS, ANTICORROSIVE PRIMER FOR "INTUMESZAIS" PAINT.



Description

Antirust primer to use previously to paint with INTUMESZAIS. Solvent : DISOLUAIS.

Aplication

Over metallic elements such as anticorrosive primer for the subsequent application of TEAIS intumescent covering INTUMESZAIS.

Surface preparation

The surface must be tightly closed, free of greases, oils, dust and other polluting agents that decreases the proper adherence on the support. Suitable to jet until SA 2 1/2 grade.

Modes of application

Stir well the content of the package before using.
Apply one coat with a recommended thickness of 35-40 microns preferably with spray gun or Airless.

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

Let it dry 24 hours and then apply INTUMESZAIS.
- Metallic surfaces must be completely free of greases ans rust. For that is recommendable the use of mechanical means such as sanding by sanding machine or particle jetting.
- Is very important that the application of the primer is done just after the cleaning of metal to avoid new corrosive process and also once the primer is dry the intumeszent paint must be applied.

Clean up

With our solvent DISOLUAIS while the product is fresh

Data sheet

Density1,5 Kg./Litre ± 0,05

Volume Solids54.4% ± 1%

Color(s)red

Touch Dry10 minutes at 20ºC/65% RH

Recoatable24 Hours at 20ºC / 65 RH.

Working temperatureFrom 8 to 30ºC

Performance

12 sqm per litre at 35 microns

Storage

2 years in their original packages tighltly closed, protected from the weather and stored in a cool and dry place.

Security



TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H340: May cause genetic defects .

H350: May cause cancer .

H372: Causes damage to organs through prolonged or repeated exposure .

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains . May produce an allergic reaction.