IMPRIMACION XP, ANTICORROSIVE PRIMER BASED ON IRON OXIDE FAST DRYING



Description

Fast dry primer for structures made of iron or steel with barrier effect. Repaintable with synthetic enamels type ESMAIS after a dry-time of 4 hours. Colours: red and grey.

Aplication

It is used for protecting against corrosion on metalic surfaces made of iron, steel, light alloys, etc. It is specially formulated for applying by spray gun. Fast dry time.

Surface preparation

The surface must be clean without dust neither greases, oils or other polluting agents that avoids a correct adherence on the supports.

Modes of application

Homegenize the content of the package before applying.
- Once cleaning up, dry, free of rust and completely free of grease one layer must be applied by gun using DISOLUAIS SOLVENT.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

- After two hours a second layer of primer can be applied.
- Apply a finishing synthetic enamel after 4 hours. The most suitable solvents are ESMAIS and ESMAR.

Clean up

With DISOLUAIS solvent while the material is wet.

Data sheet

Density1,54 kg/lt +- 0,05

Dry Film Thickness35 microns

Recoatable4 hours at 20ºC y 65% RH

Volume Solids> 63%

Working temperaturefrom 5ºC to 30ºC

Color(s)red and grey

Performance

8 sqm/l dry coal of 50 microns

Storage

2 years in their original packages tightly closed, protected from the weather and stored in cool and dry place.

Security



Indications of danger:

H226: Flammable liquid and vapour.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H340: May cause genetic defects .

H350: May cause cancer .

H372: Causes damage to organs through prolonged or repeated exposure .

H373: May cause damage to organs through prolonged or repeated exposure .

H412: Harmful to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains . May produce an allergic reaction.