LASTOIS RS, Elastomer-based waterproofing reinforcements



Description

Liquid product that is applied superficiaclly on membranes of water-based elastomer waterproofing agents (Lastois Techumbres, Lastos Cubiertas, Lastois FHCV, Teais SK Film). It improves the resistance to water decreasing water spotting.

Aplication

LASTOIS RS is used for protecting and reinforcing to waterproofing based on water-based elastomers (Lastois Techumbres, Lastois Cubieras, Lastois FHCV, Teais SK Film).

Surface preparation

The elastomer where the product is applied must be dry, clean, free of dust and particles.

Modes of application

Stir well the content of the package.
- Apply one or two layers by roller on the membrane when it is well dry.
- Let dry well the first layer before applying the second one.
- The product is ready to use.

Clean up

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

With solvent DISOLUAIS.

Data sheet

Appearancematt

Color(s)translucent

Density0,8 kg/lt

Viscosity18 +/- 6 seconds.

Performance

5 sqm/litre

Storage

One year in their original packages tightly closed and stored in cool and dry places.

Security



Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H362: May cause harm to breast-fed children.

H372: Causes damage to organs through prolonged or repeated exposure .

TEAIS

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: EUH066:Repeated exposure may cause skin dryness or cracking.

EUH208: EUH208:Contains . May produce an allergic reaction.