# ACRILAIS, HIGH STRENGTH AND DURABILITY WATERPROOFING PAINT FOR OUTDOORS




## Description

Waterproofing paint based on vinil copolymers in watery dispersion for outdoors and indoors. Smooth finishes. Can be applied on fibrecement, cement mortars, plaster before suitable primer. Basic colours.

## Aplication

In facades, inner courtyards, party walls, balconies, large fortified towers, domes, etc.
Onto fibrocement boards, cement mortar renders, gypsum, plaster, etc by priming previously.

### Surface preparation

Must be clean, without the presence of greases, oils, dust and loose particles, appearing perfectly dry.

### Modes of application

Mix the contents of the bottle well, manually or with electric mixer low rpm 300-500 rpm.
-Apply With a brush, roller or spray.
- Apply the first coating by diluting up to 10 to 15% in weight in water.
- Once the first coating is dry(after at least 12 hours), apply a second or more

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

coatings without diluting, in the same interval of time as for the first coating.
- The support must be clean, free of grease, dust or loose parts, being compact and perfectly dry, in case of using IMPRIMAIS MU primer.

## Clean up

With plentiful clean water while the paint is fresh.

# Data sheet

Density1,54 Kg./Liter ± 0,05 (varies depending on color).

Viscosity40.000 ± 10.000 mPs.a at 20ºC

Touch Dry1 Hour  /50 microns dry film/20ºC/65% of H.R.

Completely Dry24 Hours /50 microns dry film/20ºC/65% of H.R.

Recoatable12 Hours /50 microns dry film/20ºC/65% of H.R.

Appearancesmooth, matt and semi-gloss.

Color(s)white and colors according to color chart.

## Performance

Smooth: 3 sqm per kg; Semi-gloss 3 to 5 sqm per kg

## Storage

2 years, in their original packagings and properly closed, never under 5ºC temperature, stored in a cool and a dry place.

# Security

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

# Supplementary information:

EUH208: EUH208:Contains 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210: EUH210:Safety data sheet available on request.