



AUTAIS,



Description

Application

Modes of application

Data sheet

Density

Viscosity

Pigments

Dry upon touching

Dry for repainting

Colour/s

Thin layer

Solid content in volume



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:



Temperature of work

Storage

Security



Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H340: May cause genetic defects.

H350: May cause cancer.

H372: Causes damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains . May produce an allergic reaction.