EPOAIS D, EPOXY PAINT FOR SANITARY AND FOOD INDUSTRY FACILITIES



Description

Two component epoxy paint, to be mixed at the time of use ratio 85A: 15B weight. Very suitable for laboratory walls, bathrooms, kitchens, surfaces requiring good chemical resistance and ease of washing. Open time: 6 hours. Colors: White, Gray, Tile Red and Green.

Aplication

Slaughterhouses, butchers, fish markets, dairy and food industries in general, etc..
Not suitable for outdoor applications.

Surface preparation

Must be clean, without greases, dust, cracks or flakings, appearing dry and compact.

Modes of application

Once are mixed, the product has an open-time of 6 hours of length (after this time the products is liquid too but is not recommendable its use). Mix the components in the next proportions:
On weight: 85A/15B.
On volume: 3A/1B.
It is applied with a roller and brush.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en:

Priming with EPOFOS in case of metalica supports e IMPRIDUR for cementitious substrates.

Clean up

With our EPOXY SOLVENT.

Data sheet

DensityA componet 1,45 Kg./Litre at 20ºC/65%
component "B": 0,95 Kg./Lire at 20ºC/65%

Touch Dry20 minutes a 20ºC/65%

Completely DryFrom 18 to 36 Hours at 20ºC/65%

Recoatable8 Hours at 20ºC/65%

Flash Point> 15ºC TAG closed cup.

Color(s)White and others by order.

Working temperatureFrom 8 to 25ºC.

Performance

7 sqm per 50 microns layer

Storage

2 years, in their original packagings and properly closed, protected from weather and stored in a cool and dry place.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: