

## Descripción



## Application

### Modes of application

## Data sheet

Density

Solid content in volume

Dry upon touching

Dry for repainting

Dry film thickness

Aspect

Colour/s

Temperature of work

## Storage

---

## Security

---



### Indications of danger:

---

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H340: May cause genetic defects .

H350: May cause cancer .

H372: Causes damage to organs through prolonged or repeated exposure .

H412: Harmful to aquatic life with long lasting effects.

### Prudence advice:

---

P201: Obtain special instructions before use.

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

---

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

