



Descripción

Application

Modes of application

Data sheet

Density

Dry upon touching

Solid content in volume

Colour/s

Dry for repainting

Temperature of work

Storage

Security



Indications of danger:

H226: H226:Flammable liquid and vapour.

H304: H304:May be fatal if swallowed and enters airways.

H312: H312:Harmful in contact with skin.

H332: H332:Harmful if inhaled.

H315: H315:Causes skin irritation.

H360: H360Df:May damage the unborn child. Suspected of damaging fertility.

H373: H373:May cause damage to organs through prolonged or repeated exposure.

H411: H411:Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: P210:Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: P303+P361+P353:IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

