

## Description



## Application

### Modes of application

## Data sheet

Density

Viscosity

Hard dry

Thin layer

Temperature of work

## Storage

# Security



## Indications of danger:

- H225: Highly flammable liquid and vapour.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H332: Harmful if inhaled.
- H335: May cause respiratory irritation.
- H351: Suspected of causing cancer .
- H362: May cause harm to breast-fed children.
- H373: May cause damage to organs through prolonged or repeated exposure .
- H411: Toxic to aquatic life with long lasting effects.

## Prudence advice:

- P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313: IF exposed or concerned: Get medical advice/attention.
- P370+P378: In case of fire: Use ? for extinction.
- P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

---

EUH066: Repeated exposure may cause skin dryness or cracking.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email.: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

