



PINTIS LISA, WASHABLE PLASTIC PAINT FOR INDOORS - OUTDOORS



Description

Washable plastic paint for interior and exterior. On surfaces, plaster, cement, cement-based plasters, etc.. basic colors

Aplication

On ceilings and walls. On plasters and cement-based plasters, gypsum, asbestos cement, etc.

Surface preparation

Must be clean, without greases, dust, lime paint, tempera, oil and appearing compact and dry.

Modes of application

Apply using a paint brush, roller or gun.

The first coating is applied by diluting 10 to 20% in water.

The second coating is applied without diluting.

A satin finish is achieved using ACRILAIS TRASLUCIDO diluted to 30%.

IMPRIMAIS SUPER, IMPRIMAIS M.U. or IMPRIMAIS NORMAL primer is used(depending on the type of support).



Avda. da Enerxía, nº 153, PoL Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

Clean up

With plentiful clean water.

Data sheet

Density 1.6 Kg/Liter ± 0,05

Viscosity 42.500 ± 7.500 mPa.s

Dry for repainting 8 Hours/50 micron/20°C/65% of R.H.

Aspect smooth and matt.

Colour/snow white

Temperature of work 5° to 30°C

Performance

3 sqm per kg

Storage

2 años, en sus botes originales y bien cerrados protegidos de la intemperie y almacenados en lugar fresco y seco.

Security

Supplementary information:

EUH208: EUH208: Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210: EUH210: Safety data sheet available on request.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:

