PINTIS LISA, WASHABLE PLASTIC PAINT FOR INDOORS - OUTDOORS



Description

Washable plastic paint for interior and exterior. On surfaces, plaster, cement, cement-based plasters, etc.. basic colors

Aplication

On ceilings and walls. On plasters and cement-based plastes, gypsum, asbestos cement, etc.

Surface preparation

Must be clean, without greases, dust, lime paint, tempera, oil and appearing compact and dry.

Modes of application

Apply using a paint brush, roller or gun.
The first coating is applied by diluting 10 to 20% in water.
The second coating is applied without diluting.
A satin finish is achieved using ACRILAIS TRASLUCIDO diluted to 30%.
IMPRIMAIS SUPER, IMPRIMAIS M.U. or IMPRIMAIS NORMAL primer is used(depending on the type of support).

Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

Clean up

With plentiful clean water.

Data sheet

Density1.6 Kg/Liter ± 0,05

Viscosity42.500 ± 7.500 mPa.s

Recoatable8 Hours/50 micron/20ºC/65% of R.H.

Appearancesmooth and matt.

Color(s)snow white

Working temperature5º to 30ºC

Performance

3 sqm per kg

Storage

2 años, en sus botes originales y bien cerrados protegidos de la intemperie y almacenados en lugar fresco y seco.

Security

Supplementary information:

EUH208: EUH208: Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210: EUH210: Safety data sheet available on request.

TEAIS
Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo,A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es
síguenos en: