



Descripción

Water based plastic paint for exteriors. It is waterproofing, washable and resistant to bleakness. Suitable for facades, patios, party walls, etc. It can be dyed with TINTAIS. Smooth and matt finish. It complies with ASTM G53 and INCE standards on waterproofing.

Aplication

It is suitable for facades, inner courtyards, back walls, party walls, balconies, towers, domes, etc.

Surface preparation

The support of application must be clean, free of grease, dust, lime based, temper and oil based paints, by being compact and dry.

Modes of application

Homogenize properly the content of the container before using.

- IMPRIMAIS or IMPRIMAIS M.U. primer can be applied (depending on the type of support).

Apply with a paint brush, roller or gun.

The first coating is applied by diluting 10 to 20% in water.

Apply the second coating without diluting.

- For the application of the second hand the first one must be dry.
- REVETAIS can be applied with air-less tool.
- A satin finish is achieved with ACRILAIS TRANSLUCIDO diluted to 30%.
- Good resistance to damp-scrub and can be tunable with TINTAIS.
- It is waterproofing, weather resistant and washable.
- Alkali resistant and indoor waterproofing.
- Great capacity of covering and stable to the light.

Clean up

With plenty of water while the product is fresh.

Data sheet

Density 1.53 Kg/Litre \pm 0.05 at 20°C.

-Great decorative effect.

Dry film thickness 45 micron (minimum).

Viscosity 37.500 \pm 7500 at 20°C.

Dry for repainting 8 Hours/20°C/65% of R.H.

Dry upon touching Good resistance to humid friction and dyeable with TINTAIS.

Aspect smooth and matt.

Performance

3 m² per kg.

Storage

It is recommended to store this product for 2 years in tightly closed original packages protected against the weather.

Security



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teis.es

síguenos en:



Supplementary information:

EUH208: EUH208: Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210: EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

