

ESTUCAL,



Descrição

Lime stucco on paste for decorating for indoors and outdoors. For indoors must be applied as the final coat of ESTUBRIL, for outdoors must be applied ESTUPROT. The finishes appearance is smoth and shiny with marble imitation veins. It can be coloured with TINTAIS. Suitable to houses decoration, stores, offices, coffes.etc.

White and color chart available.

Aplication

Modes of application

Stiring the content of the container in order to homogenize the product properly.

-On the smooth surface based on ESTUCAL or another lime based or cement based render.

A coating smailler than a millimetre of ESTUCAL is applied with a stainless trowel.

Once dry, sand with "double zero (00)" sander.

After that another layer smaller than 1 millimetre and once flatted it will be polished with the edge of the trowel pressing hardly over ESTUCAL.

- -The suitable dry between layers has to be 24 hours more or less in order to obtain a completely dry.
- -In outdoors can be protected with ESTURBIL and in wet indoor or outdoor can be protected with ESTUPROT.

The supports have to be free of moisture. They can be painted in which case a sand will be done, and if the paint is firm and in good conditions, is enough with sanding and the dust elimination.

Data sheet

Composition





Open time

Density

Colour/s

pH value

Temperature of work

Performance

1,6 m2 per sqm

Storage

Security

Indications of danger:

H412: Harmful to aquatic life with long lasting effects.

Prudence advice:

P272: Contaminated work clothing should not be allowed out of the workplace.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:





Email.: desarrollo@teais.es

EUH208: EUH208: Contains . May produce an allergic reaction.





15143 Arteixo, A Coruña







