



# LASTOIS HIDROEXPAN, ONE COMPONENT POLYURETHANE FOR SEALING WATER LEAK CRACKS



## Description

LASTOIS HIDROEXPAN is a resin that expands in contact with water and is used for sealing cracks and joints. It expands in contact with water closing water leaks on concrete supports. It is used on retaining walls, basement, tanks, pools, etc.

## Application

In the sealing and waterproofing of cracks and cavities with water leaks. In the sealing of underground work.

## Surface preparation

Our product has good adhesion to most building materials. The application surface should be clean and free from grease and oils, being in the presence of water at the time of application of the product.

## Modes of application

Applying by injection depending on the particular works and characteristics. The injection can be done by manual or electric machine (from 5 to 100 kg/scm).

-The injection must be always done with water. The resin in contact with water polymerizes and expands itself from 6 to 10 times its volume.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: desarrollo@teais.es

síguenos en:

- Resine just polymerize resists to the most organic solvents, soft acids, alkalis and agressive microbiologic environments.

The optimum temperatures for application range between +10 and +25°C. The viscosity of the product increases at higher temperature.

## Clean up

With solvent DISOLVENTE EPOXI

## Data sheet

Density 20°C DIN 53217 1.13 gr/cm<sup>3</sup>

Viscosity 23 °C 1200 +/- 200 mPa.s

Combustion point >200°C

Composition Contains Difenilmetandiisocianate(MDI). The manipulation of the product requires precautions.

Temperature of work 10 a 25°C

Solubility Not soluble on water.

Compressive resistance 6 N /mm<sup>2</sup> (cured product)

Flexural strength resistance 1,5 N/mm<sup>2</sup> (cured product)

Adherence 1,8 N/mm<sup>2</sup> (on mortars or concretes)

Aspect Yellow-Gold colour foam with cells (solidify)

## Performance

According to the application

## Storage

1 year in their original packagings, properly closed, do not expose them to the effects of UV rays, high temperatures (+40 ° C) and in dry places cause it reticulates in contact with moisture and away from fire (even after use).



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

Telf.: 981 602 111

Fax.: 981 601 508

Email.: desarrollo@teais.es

síguenos en:



# Security



## Indications of danger:

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H351: Suspected of causing cancer.

H360: May damage fertility or the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

H412: Harmful to aquatic life with long lasting effects.

## Prudence advice:

P201: Obtain special instructions before use.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.