



## Descripción

## Aplicación

Elastic sealant resistant to temperatures up to 300 ° C, suitable for applications in construction and industry, which requires high temperature resistance in continuous regime. It can be in contact with hydrocarbons and conventional solvents at temperatures up to 200 ° C. It is very suitable for barbecues, fireplaces, forging kitchens, etc.

## Surface preparation

The application surface must be clean, dry and free of dust and loose particles.

## Modes of application

## Clean up

With clean water while material has not hardened.

# Data sheet

Density

Temperature of service

Shore A hardness

Temperature of work

Temperature of service

Resistance to traction

## Storage

1 years in their original packagings, protected from the weather, stored in a cool and dry place.

## Security



### Indications of danger:

H317: May cause an allergic skin reaction.

### Prudence advice:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.





P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## **Supplementary information:**

---

EUH208: Contains . May produce an allergic reaction.



 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
 Telf.: 981 602 111  
 Fax.: 981 601 508  
 Email.: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

