



Description

Aplication

Elastic sealant resistant to temperatures up to 300 ° C, suitable for applications in construction and industry, which requires high temperature resistance in continuous regime. It can be in contact with hydrocarbons and conventional solvents at temperatures up to 200 ° C. It is very suitable for barbecues, fireplaces, forging kitchens, etc.

Surface preparation

The application surface must be clean, dry and free of dust and loose particles.

Modes of application

Clean up

With clean water while material has not hardened.

Data sheet

Density

Temperature of service

Shore A hardness

Temperature of work

Temperature of service

Resistance to traction

Storage

1 years in their original packagings, protected from the weather, stored in a cool and dry place.

Security



Indications of danger:

H317: May cause an allergic skin reaction.

Prudence advice:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.


P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

