

## LASTOIS MS, NEUTRAL CURE SEALANT ELASTIC THAT JOINS ON WETSUPPORTS

# Descripción

Neutral cure sealant putty based on silane modified polymers. It is an odorlessproduct, free of solvents and isocyanates. Crosslinked contact with atmospheric moisture and becomes a flexible joint. It allows use on wet surfaces with good adhesion.



# Aplication

Caulk with elastic properties, which adheres to most surfaces such as building glass, aluminum, concrete, plastics, PVC, metal, wood, shingles, etc.. Allows use on damp substrates with good adhesion. Indoors or exteriores.Resist to UV radiation (except the putty colorless)

### **Surface preparation**

The application supports must be clean, free of dust and grease, or any substance that impairs adhesion.

## **Modes of application**

The surface must be completely clean, stable and resilient. It may be slightly damp.

- Cut the tip of the tube and put the nozzle into the tip, and after cut the nozzle according to the required thickness cord.

- The tube is placed in the extruder gun and pressed to release the amount of putty required depending on



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
 15143 Arteixo, A Coruña
 Telf.: 981 602 111
 Fax.: 981 601 508
 Email.: desarrollo@teais.es



the thickness of the cord to make.

- If the joint is too depth you should place a joint base Jupo, limiting that depth, which also serves as support putty

- The joint edges must be clean, firm and may be wet.

#### **Clean up**

Clean with cleaning solvent

# Data sheet

AspectThixotropic paste Density1,36 g/cm3 Temperature of work+5° to + 40 °C Shore A hardness35 Elongation until breaking point570% Colour/sWhite, gray, brown and transparent Resistance to traction2 N/mm2 CompositionSilane modified polymers

## Performance

12 ml per tube in cords of 5 mm

#### Storage

12 months in original containers protected from moisture, stored in a cool, dry place.

# **Security**



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
 15143 Arteixo, A Coruña
 Telf.: 981 602 111
 Fax.: 981 601 508
 Email.: desarrollo@teais.es



### **Indications of danger:**

H412: Harmful to aquatic life with long lasting effects.

#### Prudence advice:

- P101: If medical advice is needed, have product container or label at hand.
- P102: Keep out of reach of children.
- P103: Read label before use.
- P273: Avoid release to the environment.
- P501: Dispose of contents/container to?

#### **Supplementary information:**

EUH208: Contains . May produce an allergic reaction.



- Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
- 15143 Arteixo, A Coruña
- Telf.: 981 602 111
  Fax.: 981 601 508
- ✓ Email.: desarrollo@teais.es

