



TEAIS HOMOCOLOR, SPECIAL RESIN TO HOMOGENIZE AND PROTECT MONOLAYER MORTARS.



Description

Special resin to homogenize, enhance and protect monolayer mortar coverings. Ease of applying and high efficiency TEAIS HOMOCOLOR is specially designed for monolayer mortars with smooth or scraped finish and improving their durability.

Aplication

It is applied on coverings of monolayer mortars to level, homogenize and enhance their colours. TEAIS HOMOCOLOR also protects the wall from abrasion and wear improving its useful life and quality.

Surface preparation

The surface of application must be clean, dry and cured (concretes and mortars with more than 28 days of curing).

Modes of application

- Homogenize the content of the package correctly.
- Apply directly by brush, roller or airless.
- Avoid working on sunlight hours.



- In general one coat is enough in order to obtain the homogenizer effect. Apply two coats if it is necessary. Prime with IMPRIMAIS OR IMPRIMAIS MU according with the state of support or apply the first coat diluted between 10% to 20% in water.
- It must be applied by brush, roller or sprayer gun.
- The second hand must be applied undiluted.
- Don't apply with rain forecast, strong winds, freeze or adverse weather conditios.

Clean up

The tools must be cleaned with plenty of water while the product is wet.

Data sheet

Density 1,53 kg/lt

Viscosity 37.500 + - 7.500 at 20°C

Aspect matt

Density 1,53 kg/lt

Totally dry 12 to 18 hours at 20°C an 65% RH

Performance

3 sqm per kg.

Storage

2 years in their original packages tightly closed and protected from the weather, stored in cool and dry place.

Security

Supplementary information:



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



EUH208: EUH208:Contains . May produce an allergic reaction.

EUH210: EUH210:Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email.: desarrollo@teais.es

síguenos en:

