

TEAIS HOMOCOLOR, SPECIAL RESIN TO HOMOGENIZE AND PROTECT MONOLAYER MORTARS.



Descripción

Special resin to homogenize, enhance and protect monolayer mortar coverings.
Ease of applying and high efficiency TEAIS HOMOCOLOR is specially designed for monolayer mortars with smooth or scraped finish and improving theirs durability.

Aplication

It is applied on coverings of monolayer mortars to level, homogenize and enhance theirs colours. TEAIS HOMOCOLOR also protects the wall form abrasion and wear improving its useful life and quality.

Surface preparation

The surface of application must be clean, dry and cured (concretes and mortars with more than 28 days of curing).

Modes of application

Homogenize the content of the package correctly.

- -Apply directly by brush, roller or airless.
- Avoid working on sunlight hours.





Email.: desarrollo@teais.es

- In general one coat is enough in order to obtain the homogenizer effect. Apply two coats if it is neccesary. Prime with IMPRIMAIS OR IMPRIMAIS MU according with the state of support or apply the first coat diluted between 10% to 20% in water.
- It must be applied by brush, roller or sprayer gun.
- The second hand must be applied undiluted.
- Don't apply with rain forecast, strong winds, freeze or adverse weather conditios.

Clean up

The tools must be cleaned with plenty of water while the product is wet.

Data sheet

Density1,53 kg/lt

Viscosity37.500 + - 7.500 at 20°C

Aspectmatt

Density1,53 kg/lt

Totally dry12 to 18 hours at 20°C an 65% RH

Performance

3 sqm per kg.

Storage

2 years in their original packages tightly closed and protected from the weather, stored in cool and dry place.

Security

Supplementary information:





Email.: desarrollo@teais.es

EUH208: EUH208: Contains . May produce an allergic reaction.

EUH210: EUH210: Safety data sheet available on request.



