



TEAIS TERMOPIN, THERMAL INSULATING PAINT



Descripción

TEAIS TERMOPIN is a special paint formulated in base on special resins and insulating microbubbles. It is used for indoors and outdoors, on mortar, concrete, plaster surfaces, etc. Suitable to achieve thermic insulating properties, decreasing of condensation, decrease the thermal conductivity, energy savings, resistance to weather, improves acoustic absorption.

Aplication

It is used for indoors and outdoors on mortar, concrete, plaster surfaces, etc. When are wanted to obtain thermal insulating properties, condensation decreasing, decrease thermal conductivity, energy saving, resistance to weather and to improve acoustic absorption.

Surface preparation

The supports must be clean and dry and free of dust particles. Mortar and concreted must be cured for at least 28 days and being firm and free of any type of pollution.

Modes of application

Homogenize quite well the product because it has micro-particles which must be well distributed. The homogenization must be done by spatula. Don't use another mean of mixing in order to avoid the breaking of the microspheres.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



- The application must be done by roller or brush.
- In general, 2 or 3 coats of TEAIS TERMOPIN are required, taking into account that the thermal protection increases with each coat.
- Depending on the type of support may be necessary the application of one coat of primer using IMPRIMAIS MU or IMPRIMAIS as the case may be.

Clean up

The tools must be cleaned with plenty of water.

Data sheet

Colour/sWhite

AspectMatt

Density1,20 kg/lit

Thermal conductivitycoefficient of particles 0,14 W/mk

Performance

From 2 to 3 sqm/kg

Storage

One year in their original packages tightly closed. Protected from the weather and stored in cool and dry place.

Security

Supplementary information:

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teis.es

síguenos en:



EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

