



TEAIS SILOXANO, Waterproof paint based on siloxanes and copolymers in dispersion.



Descripción

TEAIS SILOXANO is a water-based paint based on siloxane resins highly water-repellent with high adherence and quite transpirable. It is used on mortar or concrete surfaces. The surfaces to protect with TEAIS SILOXANO mustn't be painted with other type of paints. Price of the white colour. For other colours, consult.

Aplication

TEAIS SILOXANE is used for facades and wall coverings, patio, lime facades, supports with cement-base paints, vertical surfaces where a good resistance to water is required.

Surface preparation

The support of the application must be clean, dry, free of dust or loose particles, consistent, without efflorescences. Mortars or concretes must be cured for at least 28 days

Modes of application

Homogenize well the containt of the package.

- Apply the first coat diluted in water at 10% approximately.
- Let it dry and apply the second one undiluted.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:



- The suitable temperature for the application is from 5°C to 35°C.
- Don't apply with rain forecast.
- Don't apply with strong wind or very hot surfaces exposed to direct sunlight.

Clean up

The tools must be cleaning with plenty of water while the paint is fresh.

Data sheet

Drying time 2 hours

Dry for repainting 24 hours

Density 1,48 kg/lt

Composition copolymers and siloxanes.

Storage

Un year in their original packages protected from the weather and stored in cool and dry places.

Security

Supplementary information:

EUH208: EUH208: Contains . May produce an allergic reaction.

EUH210: EUH210: Safety data sheet available on request.

