

## Descripción

New generation antirust primer, free of plumb, zinc chromate, zinc phosphate or other traditional inhibitor agents of corrosion and with a high antirust power that even allows its applying on surfaces slightly polluted by rust.



## Aplication

Aggressive environments or any application that requires a longer antirust protection in all environments.

## Surface preparation

Must be clean, free of greases, oils and other polluting agents that decrease the proper adherence on the support and a perfect finish.

## Modes of application

Shake well the content of the package to achieve a proper homogenisation.

- Because of its special formulation the product can be applied by brush or spray gun, using DISOLUAIS as a solvent in the required proportion according the used application.
- Once the first layer is dry a second one can be applied if it is required, according with each application requirements.
- Let dry completely before the application of the finish rendering.
- Existing rust must be removed from support by brush, sand or jets of particles. Dust, loose particles, greases,

oils or any substance that affects to adherence must be removed.

## Clean up

With grease-based solvent DISOLUAIS.

## Data sheet

Density 1,3 Kg./Lt.  $\pm$  0,05 at 20°C.

Solid content in volume 45,7  $\pm$  0,05 %.

Dry upon touching 20 minutes at 20°C

Hard dry 5 hours at 20°C

Dry for repainting 10 hours at 20°C

Temperature of work from 5°C to 30°C

## Performance

9 sqm per litre in 40 microns layer.

## Storage

2 years in their original packages, in a dry and cool place, tightly closed and stored in a cool and dry place.

## Security



## Indications of danger:

H226: H226: Flammable liquid and vapour.

H304: H304: May be fatal if swallowed and enters airways.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teis.es](mailto:desarrollo@teis.es)

síguenos en:



H317: H317:May cause an allergic skin reaction.

H319: H319:Causes serious eye irritation.

H336: H336:May cause drowsiness or dizziness.

H340: H340:May cause genetic defects.

H350: H350:May cause cancer.

H372: H372:Causes damage to organs through prolonged or repeated exposure.

H412: H412:Harmful to aquatic life with long lasting effects.

## Prudence advice:

---

P210: P210:Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: P303+P361+P353:IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: P308+P313:IF exposed or concerned: Get medical advice/attention.

P370+P378: P370+P378:In case of fire: Use ABC powder extinguisher for extinction.

P501: P501:Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

---

EUH066: EUH066:Repeated exposure may cause skin dryness or cracking.

EUH208: EUH208:Contains butanone oxime. May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: [desarrollo@teis.es](mailto:desarrollo@teis.es)

síguenos en:

