



Description

FIJOPI is a superficial hardener of sandstone. Produces the superficial hardening of the structure where is applied on.

Application

It is applied on all types of sandstone and several supports that can be superficially disaggregated such as coverings, mud walls, lime-mortar joints, etc.

Surface preparation

The surface must be clean, dry, free of greases, oils, free of dust and loose particles.

Modes of application

Apply only one layer, quiet spreading and preferably by sprayer gun.

- FIJOPI is just a superficial hardener. When consolidating stone works are required a previous application of ENDUPIS must be done. ENDUPIS is a geological hardener based on ethylsilicate that provides hardening in the medium and long term and subsequently finish with a layer of FIJOPI if the surface requires an immediate superficial fixing.

Clean up

With solvent DISOLUAIS.

Data sheet

Density 0,8 kg/Lt \pm 0,05 at 20 °C.

Viscosity 16 seg. A 20 °C.

Storage

2 years in their original packages tightly closed.

Security



Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H362: May cause harm to breast-fed children.

H372: Causes damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:



P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

